

# Intrepid 6M

## Sturdy aluminum RF system for 6-foot door openings

Lightweight yet tough thanks to its aluminum construction, the Intrepid 6M offers exceptional detection rate while easily fitting into any store environment.

The Intrepid 6M's Active Response System automatically adjusts the system to block interference ensuring reliable operation even in challenging environments.

### KEY FEATURES

- > Highly reliable system with high detection rate
- > Lightweight metal construction
- > Active Response System monitors store environment and automatically adjusts the system to reduce interference
- > Can be synchronized with multiple systems
- > Built-in jamming detection
- > Energy efficient - about 20W power consumption
- > Easy to use ShopMonitor Lite Dashboard for alarm event management



### SPECIFICATIONS

- > Frequency: 8.2 MHz
- > Dimensions: 15.75" W x 59.8" H x 1.97" D (40 cm x 151.9 cm x 5 cm)
- > Weight: 15.9 lbs (7.2 kg)
- > Order code: MPP400 RF TRX
- > Detection range: Up to 6' (between two pedestals)
- > Power requirement: 24V DC, 2.7A (1 power supply per pair)
- > Alarm mode: Buzzer and RGB alarm indicator
- > Operating temperature: 32° F - 95° F
- > Relative humidity range: 0 - 90%, non-condensing



**PROSEGUR**  
**SECURITY**

(800) 939-4995 // PROSEGUR.US